monostadio



UNIVERSAL CAPSULING MONOBLOCK FOR THE DISTRIBUTION AND APPLICATION OF ALL TYPES OF CAPSULES

Automatic rotary monoblock complete with:

- horizontal capsule magazine
- automatic capsule distibutor with single or multi-bell elliptical oscillating movement to transport the capsules from the magazine on to the bottle guaranteeing precise and reliable positioning
- optimum synchronization of the capsule distribution and machine functions through an encoder
- centering of the bottle neck to keep the bottle perfectly aligned and stable during positioning of the

capsule

- double head system suitable to accept interchangeable thermal, spinning or pneumatic heads dependent upon customer's requirements
- safety guards in compliance with the CE standards
- centralized control panel with variable speed inverter and PLC
- electronic system for the control of bottle flow at the infeed and exit of the machine with automatic stop and start in the event of a lack of bottles at the infeed or bottles jamming at the exit.
- chassis covered in stainless steel throughput ranging from 3,000 to 25,000 bph depending on the type of capsules to be applied Air consumption (at 6 bar) 6 liters/sec for all models

А	В	С	D	Power KW
2500	1145	2650	725	6,3
2300	1145	2500	950	8,7
2300	1145	2500	950	11,1
2600	1460	3500	950	13,5
3000	1265	3250	950	9,4
3000	1265	3250	950	11,85
3000	1265	3250	950	13,05
3200	1615	3520	950	16,7
3300	1595	3250	950	21,1
4500	2515	4440	1120	27
	2300 2300 2600 3000 3000 3000 3200 3300 4500	2300 1145 2300 1145 2600 1460 3000 1265 3000 1265 3000 1265 3200 1615 3300 1595 4500 2515	2300 1145 2500 2300 1145 2500 2600 1460 3500 3000 1265 3250 3000 1265 3250 3200 1615 3520 3300 1595 3250 4500 2515 4440	2300 1145 2500 950 2300 1145 2500 950 2600 1460 3500 950 3000 1265 3250 950 3000 1265 3250 950 3000 1265 3250 950 3200 1615 3520 950 3300 1595 3250 950

Production speed depending on the machine version: from 4000 up to 35000 b/h

